

Product Technical Data Sheet

10-12 Tamper Resistant Tri-lobe Drive Head T17

Part Number	Description	Pack Qty	Pallet Qty
6-031-0139-5MP	10-12 x 25 Tri-lobe Drive T17 Climaseal 3	1000 / 4000	288,000

Application:

Buildex® 10-12 Tri-lobe Drive Fully Threaded Type 17® is designed for Security fixings for security grilles, signs and cladding to timber where tamper resistant screws are required.

Features	Benefits
Tri-lobe Drive	For positive drive under high installation torque.
T17 Point	For easy installation into timber while ensuring maximum pullout strength and high strip torque.
Finish	Corrosion performance of Climaseal 3 to suit the application.
Colormatch	The 10-12 Type 17 can be painted to match Colorbond sheeting products.

Installation Instructions:

1. Use a Number 2 Phillips Cross Recess driver bit..
2. Use a mains powered or cordless screw driver with a drive speed of 3,000 RPM maximum.
3. Fit the driver bit into the screw and place at the fastening position.
4. Apply consistently firm pressure (end load) to the screw driver until the screw has fastened.

Drilling and Installing Capacity:

Timber F7 Pine to F27 Hardwood - minimum embedment 23.0 mm

Mechanical Properties:

Single Shear Strength (Newton) 4,700 | Axial Tensile (Newton) 8,800 | Torsion Strength 7.2 Newton-metre

Pullout Values (Newton):

F7 (Pine) Timber, 23 mm embedment: 3,800 | F17 (Hardwood) Timber 23 mm embedment: 5,200

All values are averages obtained under laboratory conditions and appropriate safety factors should be applied for design purposes. These figures are applicable to Buildex® head marked product only.


Material: Carbon Steel SAE 1022 | **Heat Treatment:** To AS 3566.1 | **Finish:** Climaseal 3®

Corrosion Performance:

Climaseal 3 Fasteners are suitable for use in Category 3 corrosive environments as described in ISO 9223-2012 and AS4312-2008

Product Technical Data Sheet

10-12 Tamper Resistant Tri-lobe Drive Head T17



Part Number	Description	Length	Runout
6-031-0139-5MP	10-12 x 25 Tri-lobe Drive T17 Climaseal 3	23.5 / 25.0	2.7 Max.

All dimensions nominal unless otherwise stated. Normal manufacturing tolerances apply. All dimensions in millimeters. Third Angle Projection. Scale Full Size

Buildex® Head Office
 600 South Road
 Moorabbin Victoria 3189
 Australia

1300 368 101
 CustomerService-MBN@buildex.com.au

Technical Help Desk
 Technicalhelpdesk@buildex.com.au