Product Technical Data Sheet

14-10 Bugle Batten Part Thread Stainless Grade 304 Type 17

Part Number	Description	Pack Qty	Pallet Qty
6-032-0044-2	14-10 x 75 Bugle Batten Part Thread Stainless Grade 304 Type 17	500	52,000
6-032-0045-3	14-10 x 100 Bugle Batten Part Thread Stainless Grade 304 Type 17	500	26,500

Application:

Buildex® 14-10 Bugle Batten Head, grade 304 stainless steel Type 17 screws are designed for fixing roof battens to timber rafters, or fixing heavy timbers where a flush finish is required - fencing - furniture - pergolas and boardwalks where high levels or corrosion are likely.

Features	Benefits
5mm Hex Drive	For positive drive under high installation torque.
T17 Point	For easy installation into timber while ensuring maximum pullout strength and high strip torque.
Stainless Steel	Corrosion performance of Stainless Steel to suit the application.

Drilling and Installing Capacity:

Timber F7 Pine to F27 Hardwood - miniumum embedment 35.0 mm

Mechanical Properties:

Single Shear Strength (Newton) 10,200 | Axial Tensile (Newton) 12,600 | Torsion Strength 12.7 Newton-metre

Pullout Values (Newton):

F7 (Pine) Timber, 35 mm embedment: 3,820 | F17 (Hardwood) Timber 35 mm embedment: 6,980

All values are averages obtained under laboratory conditions and appropriate safety factors should be applied for design purposes.
These figures are applicable to Buildex® head marked product only.

Material: Stainless Steel Grade 304 (A2) | **Heat Treatment:** Nil | **Finish:** Stainless Steel

Corrosion Performance: Stainless Steel Grade 304 (A2)

Whilst every care was taken in preparation of this guide, Buildex® accepts no responsibility for the accuracy of the information supplied. Copyright 2017. The contents of this document are the exclusive copyright of Buildex® and may not be reproduced without written permission.